

Research Brief 193: Accelerating Pump-and-Treat Remediation at Arsenic-contaminated Sites

Release Date: 1/05/2011



<http://www.niehs.nih.gov/srp/>

Background

“Pump-and-treat” remediation strategies involve pumping contaminated groundwater to the surface using a series of extraction wells, treating the groundwater to remove the contaminants, and then either re-injecting the water underground or disposing of it off site. Although sites utilizing pump-and-treat are expected to need many years to reach desired clean up levels and have high annual cost, this approach is in use at nearly three-quarters of the Superfund sites where groundwater is contaminated.

The Vineland Chemical Company, located in southern New Jersey, manufactured arsenic-based herbicides from 1950 to 1994. Decades of improper storage and disposal led to extensive arsenic contamination of subsurface soils, groundwater, and adjacent creeks, rivers and wetlands. A two million gallons per day pump-and-treat remediation facility, operating since 2000 at the Vineland Superfund Site, has significantly reduced offsite arsenic transport and yielded a ten-fold initial decrease in groundwater total arsenic concentrations in the pumping wells. However, groundwater arsenic levels remain high (several hundred $\mu\text{g}/\text{L}$) and the sandy aquifer solids represent a large reservoir of arsenic (~105 kilograms) for continued groundwater contamination.

Arsenic is identified as a groundwater contaminant at 565 National Priority List sites.

The effectiveness of pump and treat systems for remediation of arsenic-contaminated groundwater is affected by aquifer conditions (e.g., pH, oxidation-reduction potential) and subsurface geology. In particular, the relatively slow release of arsenic from iron and aluminum (hydr)oxides on the surface of aquifer solids can greatly decrease the effectiveness of pump and treat systems.

Advances

Columbia University scientists funded by the NIEHS Superfund Research Program hypothesized that the time frame for remediating arsenic contaminated aquifers via pump-and-treat could be substantially decreased by subsurface additions of chemical amendments. The goal is to increase the mobilization of arsenic from aquifer solids and therefore increase the amount of arsenic removed from the aquifer with each volume of water pumped out and treated.

The scientists combined laboratory experiments, hydrological modeling, and field studies to evaluate the efficacy of chemical amendments for mobilizing arsenic from aquifer solids. The most promising chemical amendment has been oxalic acid, a natural soil acid often responsible for dissolving and transporting iron and aluminum oxides in unsaturated zone soils. These oxide phases are also important on aquifer mineral surfaces.



Bench top column experiments with Vineland aquifer solids



Field study set up

Laboratory column experiments using arsenic-contaminated aquifer solids (~80 ppm arsenic) from Vineland suggest that oxalic acid can be effective at significantly increasing arsenic mobility. Compared to 5% release when flushing with groundwater alone, >85% of the arsenic was removed from the aquifer solids with a 10 mM oxalic acid treatment. More importantly, extrapolations using these data suggest that chemical treatments could lower the Vineland Superfund Site cleanup time-scale from ~600 years with ambient groundwater alone to ~4 years with 10 mM oxalic acid, based on the cleanup goal of lowering the arsenic on the aquifer solids to less than 20 mg/kg.

During 2008 and 2009, the Columbia University scientists carried out modeling and in situ field experiments using tracers and subsurface chemical

amendments to build on these laboratory results. Modeling groundwater flow and transport at the site helped design optimal locations for injection and observation wells; amendment and tracer concentrations; injection rates; and pumping rates for these experiments. In 2009, the scientists injected oxalic acid and two tracers (bromide and SF6) into a small portion (~50 m²) of the Vineland site. Groundwater samples suggest that introduction of oxalic acid led to increased arsenic release at an observation well and the nearby pump and treat recovery well. The total amount of arsenic recovered from the two wells was ~3 kg, approximately the amount of contaminant arsenic within the pilot study area.

The Columbia scientists also plan to investigate several basic science questions directed towards both the mechanisms by which the oxalic acid mobilizes arsenic as well as the eventual rates of microbial degradation and sorption of oxalic acid. Future work will investigate issues related to scaling the chemical additions to larger portions of the site.

Significance

Oxalic acid shows promise for dramatically decreasing the time required to use pump-and-treat intervention to remediate not only the Vineland Megasite, but other sites where contaminants are primarily associated with iron and aluminum oxide surfaces.

This would be an important innovation because traditional pump-and-treat technologies can be quite expensive. A 2003 survey of annual operation and maintenance costs at pump-and-treat sites reported a mean annual cost of ~\$0.6M, with the Vineland Superfund pump and treatment costs at that time being the highest surveyed at \$4M/yr.

For more information, contact:

Steven Chillrud

Lamont-Doherty Earth Observatory of Columbia University
61 Rt 9W
Palisades, NY 10964
Telephone: (845) 365-8893
Email: chilli@ldeo.columbia.edu

Martin Stute

Department Environmental Sciences at Barnard College and
Columbia University
Telephone: (845) 365-8704
Email: martins@ldeo.columbia.edu

Brian Mailloux

Department Environmental Sciences at Barnard College
Palisades, NY 10964
Telephone: (212) 854-7956
Email: bmaillou@barnard.edu

To learn more about this research, please refer to the following sources:

Wovkulich, K., Mailloux, B. J., Lacko, A., Keimowitz, A. R., Stute, M., Simpson, H. J., Chillrud, S.N., 2010. Chemical Treatments for Mobilizing Arsenic from Contaminated Aquifer Solids to Accelerate Remediation. *Applied Geochemistry* 25:1500–1509. PMID: PMC2976553. doi:10.1016/j.apgeochem.2010.08.001

